

Council Carpark Lighting B160.04



RFL530-SE

DESIGN STATEMENT

Park lighting is used to illuminate Council-owned carpark. The LED light provides improved energy efficiency.

Higher lighting level for dedicated disabled parking maybe provided if applicable.

APPLICABLE LOCATION

Council carpark.

COUNCIL STANDARD DRAWING

N/A

CROSS REFERENCE DOCUMENT

- AS 1158.6 Lighting for Roads and Public Spaces (Part 6: Luminaires), category P4.

STANDARD SPECIFICATION

Luminaire: RFL530-SE (LED) from WE-EF. 'Classic Silver' 2-pack paint finish Or VFL530-SE(LED)

Light distribution: Lenses for light distribution will need to be specified for each project.

Colour temperatures: Colour temperatures of 4000K will need to be specified for each project.

Pole: Galvanised finish or unless specified, 'Classic Silver' 2-pack paint finish.

Height: Minimum luminaire mounting height should be 6 metres.

SUPPLIER

WE-EF www.we-ef.com.au or similar.

Distributor: Buckford Illumination www.buckford.com.au or similar.

MAINTENANCE

Lighting within Council carpark is metered lighting, maintained by Public Lighting Officer.



RFL530-SE

GENERAL NOTES

1. Refer to manufacturer's installation manual

B160.04 Council Carpark Lighting

